



DD Models (Fin Space 6.0 mm)

Model	Capacitykw DT=7K t ₀ =-7°C		Aream ²	Tube Vdm ³	Air Flowm ³ /h	Air Throwm	Fan InputW	Defrosting W		Pipe dia mm		Drainage dia
	R22	R404A						Coil	Rever	Liquid	Gas	
DD1. 4/311A	1. 4	1. 5	5. 5	1. 4	1500	9	90	1. 0	0. 5	φ12	φ16	1"
DD2. 3/311A	2. 3	2. 4	8. 5	2. 4	1500	9	90	1. 5	0. 5	φ12	φ19	1"
DD3/312A	3	3. 2	11	3. 1	3000	9	180	1. 8	0. 9	φ12	φ22	1"
DD4. 5/312A	4. 5	4. 7	20	4. 4	3000	9	180	2. 7	0. 9	φ12	φ22	1"
DD6/352A	6	6. 3	27	6. 1	4500	10	280	2. 7	0. 9	φ16	φ22	1"
DD7. 5/402A	7. 5	7. 9	33	7. 9	7000	13	360	4. 8	1. 2	φ16	φ22	1"
DD9/402A	9	9. 5	40	9. 4	7000	13	360	6. 0	1. 2	φ16	φ28	1"
DD11/402A	11	11. 6	47	11	7000	13	360	7. 2	1. 2	φ16	φ28	1"
DD15. 5/502A	15. 5	16. 3	67	15. 6	12000	17	900	7. 5	3. 0	φ22	φ35	1"
DD19/453A	19	20	80	19. 1	13500	17	750	8. 0	4. 0	φ22	φ35	1"
DD24/503A	24	25. 2	94	22. 4	18000	19	1350	10. 0	4. 0	φ22	φ42	1"
DD29/503A	29	30. 5	120	25. 6	18000	19	1350	12. 0	4. 0	φ22	φ54	1"
DD32/503A	32	33. 6	140	32	18000	19	1350	14. 0	4. 0	φ22	φ54	1"
DD38/504A	38	39. 9	160	38. 7	24000	19	1800	14. 0	5. 2	φ22	φ54	1"
DD47/554A	47	49. 4	200	45. 1	30000	25	2400	15. 6	5. 2	φ22	φ54	1"
DD58/554A	58	60. 9	235	58	30000	25	2400	20. 8	5. 2	φ28	φ54	1"
DD72/604A	72	75. 6	285	70. 9	42000	25	3120	26. 0	5. 2	φ35	φ60	1"
DD79/634A	79	83	300	77. 3	46000	25	3200	28. 6	5. 2	φ35	φ60	1"
DD88/634A	88	92. 4	356	83. 7	46000	28	3200	33. 8	5. 2	φ35	φ60	1"